

Koncovka nízkotlaká AGR MS

Použitie: Pre vzduchové a vodné hadice


Tesnenie: 45° kužel

Norma: DIN 2999 / ISO 228

Materiál: Mosadz

Pracovný tlak: 12 bar

Poznámka: NT 25 AGR MS
má tesniaci kužel 37°



Značenie	Priemer nátrubku		Prípoj. závit G	Sest'hran Sw [mm]	Vrtanie d [mm]	Dĺžka		
	DN [mm]	DN [inch]				L [mm]	Ln [mm]	Lz [mm]
NT 06 AGR MS 04	6	1/4"	G 1/8"	14		33	22	7
NT 06 AGR MS	6	1/4"	G 1/4"	17		35	22	9
NT 06 AGR MS 09	6	1/4"	G 3/8"	19		36	22	9
NT 06 AGR MS 13	6	1/4"	G 1/2"	24		41	25	10
NT 08 AGR MS 06	8	5/16"	G 1/4"	17		35	22	9
NT 09 AGR MS 04	9	3/8"	G 1/8"	14		33	22	7
NT 09 AGR MS 06	9	3/8"	G 1/4"	17		35	22	9
NT 09 AGR MS	9	3/8"	G 3/8"	19		36	22	9
NT 09 AGR MS 13	9	3/8"	G 1/2"	24		40	22	10
NT 10 AGR MS 06	10	3/8"	G 1/4"	17		35	22	9
NT 13 AGR MS 06	13	1/2"	G 1/4"	17		42	28	9
NT 13 AGR MS 09	13	1/2"	G 3/8"	19	11	42	28	9
NT 13 AGR MS	13	1/2"	G 1/2"	24	11	46	28	11
NT 13 AGR MS 19	13	1/2"	G 3/4"	32		52	28	16
NT 19 AGR MS 13	19	3/4"	G 1/2"	24		54	36	12
NT 19 AGR MS	19	3/4"	G 3/4"	32		60	35	16
NT 25 AGR MS	25	1"	G 1"	36		59	38	17

PREDAJ: HADICE, SPONY, RÝCHLOSPOJKY, KONCOVKY, OPLETY, ŠRÚBENIA, HNACIE REMENE, REŤAZE A SPOJKY, GUFERÁ, O-KRÚŽKY, MANŽETY, TESNIACA GUMA, LOŽISKÁ A PRÍSLUŠENSTVO, MAZACIA TECHNIKA...

VÝROBA: HADICE S KONCOVKAMI (hydraulika. pneumatika, klimatizácia, mazanie, meranie)

