

Koncovka vysokotlaká DKJ


Použitie: Pre hydraulické hadice

Tesnenie: 74° kužel

Norma: JIC

Materiál: Oceľ povrchovo upravená

Pracovný tlak: Maximálne do tlaku
odpovedajúceho hadici
podľa normy 4SP



Značenie	Priemer nátrubku		Závit	Sest'hran Sw [mm]
	[mm]	[inch]		
DN 04 DKJ 06	04	3/16"	7/16"-20	14,15
DN 06 DKJ	06	1/4"	7/16"-20	14,15
DN 06 DKJ 04	06	1/4"	3/8"-24	14
DN 06 DKJ 08	06	1/4"	1/2"-20	17
DN 06 DKJ 10	06	1/4"	9/16"-18	19
DN 08 DKJ	08	5/16"	1/2"-20	17
DN 08 DKJ 10	08	5/16"	9/16"-18	19
DN 08 DKJ 13	08	5/16"	3/4"-16	24
DN 10 DKJ	10	3/8"	9/16"-18	19
DN 10 DKJ 08	10	3/8"	1/2"-20	17
DN 10 DKJ 13	10	3/8"	3/4"-16	24
DN 10 DKJ 16	10	3/8"	7/8"-14	27
DN 13 DKJ	13	1/2"	3/4"-16	24
DN 13 DKJ 10	13	1/2"	9/16"-18	19
DN 13 DKJ 16	13	1/2"	7/8"-14	27
DN 13 DKJ 20	13	1/2"	1"1/16-12	32
DN 16 DKJ	16	5/8"	7/8"-14	27
DN 16 DKJ 20	16	5/8"	1"1/16-12	32
DN 20 DKJ	20	3/4"	1"1/16-12	32
DN 20 DKJ 25	20	3/4"	1"5/16-12	38,41
DN 25 DKJ	25	1"	1"5/16-12	38,41
DN 25 DKJ 32	25	1"	1"5/8-12	50
DN 32 DKJ	32	1"1/4"	1"5/8-12	50
DN 32 DKJ 40	32	1"1/4"	1"7/8-12	60
DN 40 DKJ	40	1"1/2"	1"7/8-12	60

PREDAJ: HADICE, SPONY, RÝCHLOSPOJKY, KONCOVKY, OPLETY, ŠRÚBENIA, HNACIE REMENE, REŽAZE A SPOJKY GUFERÁ, O KRÚŽKY, MANŽETY, TESNIACA GUMA, LOŽISKÁ A PRÍSLUŠENSTVO, MAZACIA TECHNIKA

VÝROBA: HADICE S KONCOVKAMI (hydraulika, motorové palivá, vzduch)