

Ochranný oplet SGF

Použitie: Ochrana hadice pred mechanickým poškodením a sálavým teplom

Materiál: Ocelový drôt povrchovo upavený



Značenie	Priemer		Stena [mm]	Polomer ohybu [mm]
	vnútorný [mm]	vonkajší [mm]		
SGF 06	6,0	8,0	1,00	20
SGF 07	7,0	9,0	1,00	20
SGF 08	8,0	10,0	1,00	25
SGF 10	10,0	13,0	1,50	25
SGF 13	13,0	16,0	1,50	35
SGF 15	15,0	18,0	1,50	40
SGF 18	18,0	21,3	1,65	45
SGF 19	19,0	23,0	2,00	45
SGF 20	20,0	24,0	2,00	50
SGF 22	22,0	27,0	2,50	55
SGF 24	24,0	29,0	2,50	60
SGF 26	26,0	30,0	2,00	60
SGF 28	28,0	32,0	2,00	63
SGF 30	30,0	34,0	2,00	65
SGF 32	32,0	36,0	2,00	75
SGF 35	35,0	39,5	2,25	80
SGF 38	38,0	43,5	2,75	85
SGF 42	42,0	47,5	2,75	88
SGF 44	44,0	49,5	2,75	90
SGF 45	45,0	50,5	2,75	90
SGF 48	48,0	53,5	2,75	95
SGF 50	50,0	56,0	3,00	115
SGF 52	52,0	58,0	3,00	115
SGF 55	55,0	61,0	3,00	115
SGF 58	58,0	64,0	3,00	117
SGF 60	60,0	66,0	3,00	120
SGF 62	62,0	69,0	3,50	125
SGF 65	65,0	72,0	3,50	130
SGF 68	68,0	74,0	3,00	140
SGF 70	70,0	77,0	3,50	150
SGF 72	72,0	79,0	3,50	160
SGF 76	76,0	83,0	3,50	166
SGF 80	80,0	87,0	3,50	170
SGF 84	84,0	92,0	4,00	180
SGF 90	90,0	100,0	5,00	190
SGF 94	94,0	104,0	5,00	200

PREDAJ: HADICE, SPONY, RÝCHLOSPOJKY, KONCOVKY, OPLETY, ŠRÚBENIA, HNACIE REMENE, REŤAZE A SPOJKY GUFERÁ, O KRÚŽKY, MANŽETY, TESNIACA GUMA, LOŽISKÁ A PRÍSLUŠENSTVO, MAZACIA TECHNIKA

VÝROBA: HADICE S KONCOVKAMI (hydraulika, motorové palivá, vzduch)