

## Ochranný oplet SSR

**Použitie:** Ochrana hadice pred mechanickým poškodením

**Materiál:** Oceľový drôt povrchovo upavený



Značenie	vnútorný [mm]	Priemer vonkajší [mm]	drôt [mm]
SSR 13-2	13	17	2,0
SSR 14-2	14	18	2,0
SSR 15-2	15	19	2,0
SSR 16-2	16	20	2,0
SSR 18-2	18	22	2,0
SSR 20-2	20	24	2,0
SSR 22-2	22	26	2,0
SSR 23-2	23	27	2,0
SSR 24-2	24	28	2,0
SSR 25-2	25	29	2,0
SSR 26-2	26	30	2,0
SSR 27-2	27	31	2,0
SSR 27-2,5	27	32	2,5
SSR 28-2	28	32	2,0
SSR 30-2	30	34	2,0
SSR 32-2	32	36	2,0
SSR 34-3	34	40	3,0
SSR 38-3	38	44	3,0
SSR 40-3	40	46	3,0
SSR 41-3	41	47	3,0
SSR 42-3	42	48	3,0
SSR 48-3	48	54	3,0
SSR 51-3	51	57	3,0
SSR 52-3	52	58	3,0
SSR 54-3	54	60	3,0
SSR 56-3	56	62	3,0
SSR 60-3	60	66	3,0
SSR 68-3	68	74	3,0
SSR 72-3	72	78	3,0
SSR 73-3	73	79	3,0