


Redukcia vonkajší/vnútorný závit RV AGIG MS**Použitie:** Pre vzduchové a vodné rozvody**Materiál:** Mosadz**Pracovný tlak:** 12 bar

Značenie	Vonkajší závit G1	Vnútorný závit G2	Sest'hran Sw [mm]
RV AGIG MS G1/4"-G1/8"	G 1/4"	G 1/8"	17
RV AGIG MS G3/8"-G1/4"	G 3/8"	G 1/4"	19
RV AGIG MS G1/2"-G1/4"	G 1/2"	G 1/4"	21
RV AGIG MS G1/2"-G3/8"	G 1/2"	G 3/8"	21
RV AGIG MS G3/4"-G1/2"	G 3/4"	G 1/2"	32
RV AGIG MS G1"-G1/2"	G 1"	G 1/2"	36

PREDAJ: HADICE, SPONY, RÝCHLOSPOJKY, KONCOVKY, OPLETY, ŠRÚBENIA, HNACIE REMENE, REŤAZE A SPOJKY, GUFERÁ, O-KRÚŽKY, MANŽETY, TESNIACA GUMA, LOŽISKÁ A PRÍSLUŠENSTVO, MAZACIA TECHNIKA...**VÝROBA:** HADICE S KONCOVKAMI (hydraulika. pneumatika, klimatizácia, mazanie, meranie)